Tidel Series 4e

The Tidel Series 4e offers industry-leading expansion capabilities that retail organizations require to manage their day-to-day cash management business. The Tidel Series 4e and supported peripherals enable retail organizations to recycle coins, dispense coins and notes, and scale their note deposit and validation capabilities. By supporting these peripherals, the Tidel Series 4e is the only choice for retail organizations that require end-to-end cash management solutions that address a diverse set of needs. Refer to the peripheral options below to find the solutions that work best for your business. Then use our Series 4e Configuration Tool to configure a system that best meets your needs.

EXPANSION CAPABILITIES FOR NOTE DISPENSING, COIN DISPENSING AND RECYCLING, AND NOTE VALIDATION

The Tidel Series 4e offers industry-leading expansion capabilities that enable retail organizations to recycle coins, dispense coins and notes, and scale their note deposit and validation capabilities. By supporting these peripherals, the Tidel Series 4e is the only choice for retail organizations that require end-to-end cash management solutions that address a diverse set of needs.

CONNECTIVITY AND UPGRADEABILITY

The Series 4e and supported peripherals connect via data cables that are provided with each system. The cables are offered in up to 100' lengths, which enable unparalleled flexibility when placing the systems in a store environment. In addition, by offering this connectivity method, peripherals can be purchased and deployed after a Series 4e has been placed in a store, enabling a simple and effective upgrade path.



TIDEL SERIES 4E SUPPORTED PERIPHERALS



Bulk Coin Dispenser 6 cup and 8 cup



Rolled Coin Dispenser



Bulk Coin and Note Dispenser



Low Capacity Note Dispenser



High Capacity Note Dispenser (3-high)



High Capacity Note Dispenser (4-high)



Sido Co



Aedium Coir

Tidel Series 4e

Specifications



Model:

Tidel Series 4e

Standard Version:

Weight: 96 lbs. (43 kg) Height: 18" (457 mm) Width: 12.25" (311 mm) Depth: 19" (483 mm) vault only Depth: 23" (584 mm) overall

XL Version

Weight: 121 lbs. (55 kg) Height: 18" (457 mm) Width: 12.25" (311 mm) Depth: 24.5" (622 mm) vault only Depth: 28.5" (724 mm) overall



Tidel Series 4e with Storage Vault

149 lbs. (68 kg) 30.75" (781 mm) 12.25" (311 mm) 19" (483 mm) vault only 23" (584 mm) overall

174 lbs. (79 kg) 30.75" (781 mm) 12.25" (311 mm) 24.5" (622 mm) vault only 28.5" (724 mm) overall



Tidel Series 4e with Mailbox Drop Vault

156 lbs. (70 kg) 30.75" (781 mm) 12.25" (311 mm) 19" (483 mm) vault only 23" (584 mm) overall

181 lbs. (82 kg) 30.75" (781 mm) 12.25" (311 mm) 24.5" (622 mm) vault only 28.5" (724 mm) overall



Tidel Series 4e with Pedestal

126 lbs. (57 kg) 30.75" (781 mm) 12.25" (311 mm) 19" (483 mm) vault only 23" (584 mm) overall

151 lbs. (68 kg) 30.75" (781 mm) 12.25" (311 mm) 24.5" (622 mm) vault only 28.5" (724 mm) overall

Hardware Features

- 7" Color console screen
- Power supply and main CPU board accessible via the console
- 3 bottom options storage vault (includes drop slot), mailbox drop vault, or pedestal
- Support for single or bulk note validators
- Support for standard (1,200 notes) or XL (2,250 notes) cassettes
- Personal Identification Number (PIN) and/or iButton allows managed access to functions, reports, and
- Note validator maintenance door enables validator heads to be removed in the event of a note jam
- Integrated thermal printer with receipt cutter
- RoHS Compliant/CE, UL Certified
- Connectivity to supported peripherals via provided data cables

Software Features

- All bulk coin dispense transactions are completely auditable and managed by individual user PIN
- Buy Change function allows for the exchange of a note for bulk change
- Includes a complete cash management application
- Advanced accounting features allow for extensive list of reports
- Supports network downloads for software upgrades or for new currency releases
- Can be connected to Ethernet network for interface to POS, back office PC, or remote locations
- Remote reports can be downloaded using an Ethernet or optional cellular connection

Warranty

- 1 year parts and 90 days labor (inside the US)
- 1 year parts only (outside the US)

Power Requirements

120 VAC 60Hz or 220 VAC 50Hz

